

Order from Allstrap 866-779-2673



Distributed By:
Allstrap

1719 Kenny Rd
Columbus, OH, 43212

A334

***Manual sealless steel
strapping tool***



A334

Manual sealless steel strapping tool

Strapping qualities	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi	
Strapping dimensions:	widths	16.0 – 20.0 mm / ⁵ / ₈ - ³ / ₄ "
	thicknesses	0.58 – 0.80 mm / .023 – .031"
Weight	7.2 kg / 15.9 lbs	
Average seal strength	approx. 80 %	

The advantages

- sealless combination tool to strap heavy flat packages (e.g. steel-, metal- and forest product industry, with max. strap thickness 0.80 mm / .031")
- permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- the sealless joint reduces the overall strapping costs by approx. 10 % through the elimination of the seals



Chart of types Model A334

Item. No.	Model	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.2590	A334/16/0.58-0.70	16	⁵ / ₈ "	0.58 – 0.70	.023 - .028
13.2591	A334/16/0.80	16	⁵ / ₈ "	0.80	.031
13.2610	A334/19/0.58-0.70	19	³ / ₄ "	0.58 – 0.70	.023 - .028
13.2611	A334/19/0.80	19	³ / ₄ "	0.80	.031
13.2620	A334/20/0.58-0.70	20		0.58 – 0.70	.023 - .028
13.2621	A334/20/0.80	20		0.80	.031

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi
 Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

