

Manual sealless steel strapping tool

**Characteristics**

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	widths 16.0 – 20.0 mm / ⁵ / ₈ – ³ / ₄ "
thicknesses	0.58 – 0.80 mm / .023 – .031"
Weight:	7.2 kg / 15.9 lbs
Average seal strength:	approx. 80 %

Advantages

- Sealless combination tool to strap heavy flat packages (e.g. steel-, metal- and forest product industry, with max. strap thickness 0.80 mm / .031")
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10 % through the elimination of the seals

Distributed By:
Allstrap1719 Kenny Rd
Columbus, OH, 43212

Chart of types model A334

Item No.	Model	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.2590	A334/16/0.58-0.70	16	5/8"	0.58-0.70	.023-.028
13.2591	A334/16/0.80	16	5/8"	0.80	.031
13.2610	A334/19/0.58-0.70	19	3/4"	0.58-0.70	.023-.028
13.2611	A334/19/0.80	19	3/4"	0.80	.031
13.2620	A334/20/0.58-0.70	20		0.58-0.70	.023-.028
13.2621	A334/20/0.80	20		0.80	.031

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi
 Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

Distributed By:
Allstrap
 1719 Kenny Rd
 Columbus, OH, 43212