



The most experienced
tool designers in the industry
introduce the next generation...

ZL25

**MANUAL SEALLESS
COMBINATION TOOL
FOR STEEL
STRAPPING WITH
"Z-LOCK" REVERSE
LOCKING SYSTEM**



The only available manual tools with an easy to use reverse locking system. Our exclusive "Z-Lock" reverse locking system is designed for the most demanding applications. It provides added protection against the loosening or unlocking of the sealless connection in either direction.

These tools are designed for the strapping of concrete products, crates, lumber, metal products, palletized products as well as other products to be unitized with steel strapping.

The ZL25 series tools are specifically designed for use with high tensile steel strapping (of up to 156,000 psi / 1100 N/mm²) and may also be used with regular duty strapping for much improved durability. For use with strapping sizes from 1/2" x *.015" (13 mm x 0.38 mm) to 3/4" x .025" (19 mm x 0.635 mm).

The proven patented design provides much improved seal joint efficiency, while at the same time requiring 30 to 40 % less effort compared with other tools in its category.

With the fewest individual parts and components, less maintenance and repair is required compared with other tools in its category.

Replacement of parts is very simple and it takes only a few minutes to replace the feedwheel, gripper, knife, punch or die.

Manufactured from only the most durable materials, this tool provides

Distributed By:
Allstrap

1719 Kenny Rd
Columbus, OH, 43212

unsurpassed reliability.

TECHNICAL SPECIFICATIONS

Model Number	Strap Width	Strap Thickness
ZL25-1	1/2" (13 mm)	*.015" - .025" (0.635 mm - 0.635 mm)
ZL25-2	5/8" (16 mm)	*.015" - .025" (0.635 mm - 0.635 mm)
ZL25-3	3/4" (19 mm)	*.015" - .025" (0.635 mm - 0.635 mm) *.015" - .019" (0.38 mm - 0.48 mm) requires knife replacement only.

Weight	10.6 lbs (4.8 kg)
Base Length	4.2" (105 mm)
Base Width	2.4" (60 mm)
Height	4.2" (105 mm)

[Click here to Print](#)

Distributed By:

Allstrap

1719 Kenny Rd
Columbus, OH, 43212